

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of North Boundary,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15164

CHAINS
53.35

Creek, 2 lks. wide, course N. 20° W.; asc. 95 ft. over NE. slope.

56.35

Spur, slopes N. 10° E.; desc. 50 ft. over NW. slope.

60.335

Point for the W 1/16 sec. cor. of sec. 31 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

W 1/16 S 31
1971

from which

A fir, 6 ins. diam., bears N. 33° E., 12 lks.
dist. mkd. W 1/16 S31 BT.

A fir, 8 ins. diam., bears N. 32° W., 6 lks.
dist., mkd. W 1/16 S31 BT.

Descend 220 ft. over NW. slope.

80.06

The cor. of Tps. 25 and 26 S., Rs. 7 and 8 W., re-established under Group No. 739, concurrently with this resurvey, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 25 S
R 8 W R 7 W
S 36 | S 31
S 1 | S 6
T 26 S
1971

from which

A fir, 10 ins. diam., bears N. 22° E., 87 lks.
dist., mkd. T25S R7W S31 BT.

A fir, 15 ins. diam., bears S. 49° E., 44 lks.
dist., mkd. T26S R7W S6 BT.

A fir, 20 ins. diam., bears S. 14° W., 52 lks.
dist., mkd. T26S R8W S1 BT.

A fir, 10 ins. diam., bears N. 45° W., 23 lks.
dist., mkd. T25S R8W S36 BT.

Land, mountainous.

Soil, clay loam.

Timber, fir, hemlock, cedar, madrone, alder, maple, and chinquapin; undergrowth, vine maple, salal, fern, rhododendron, and poison oak.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 26 S., R. 7 W., Willamette Meridian, Oregon.

(Restoring the survey by Dennis Hathorn,
Deputy Surveyor, in 1855, and
the survey by Addison R. and Samuel C. Flint,
Deputy Surveyors, in 1881.)
