

County Surveyor's Record, Douglas County, Oregon

.Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15166

CHAINS

From this same point, the 1/4 sec. cor. of secs. 34 and 35, bears S. 0° 07' E., 40.02 chs. dist., determined at record bearing and distance from the remains of an original bearing tree:

A white oak stump, 26 ins. diam., bears S. 16° E., 260 lks. dist., with old axe marks visible on decayed blaze.

At the corner point

*FD. OK D. BENTZ 11/91
M 112-51 (S.W. COR LOT 88)*

Drive an iron pin, 6 ins. long, 5/8 in. diam., 6 ins. in the ground, level with road surface.

The corner is located in center of W. lane of Elgarose Road, paved, 40 lks. wide, bears N. and S.

From this point, a reference monument, established by the Douglas County Surveyor, in 1971, bears East, 0.75 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 26 S R 7 W
1/4
S 34 | S 35
WIT. COR. 50 FT. W.
1971

from which

A fir, 16 ins. diam., bears S. 9° E., 87 lks. dist., with scribe marks WC 1/4 S35 CS BT. visible on open blaze.

A white oak, 9 ins. diam., bears S. 58° E., 110 lks. dist., with scribe marks WC 1/4 S35 CS BT visible on open blaze.

N. 0° 01 E., bet. secs. 26 and 27, marking and blazing the true line.

Ascend 125 ft. over general SE. slope, along gravelled road, 12 lks. wide, bears N. and S.

21.30 Leave gravelled road, bears N. 40° W., and S.; enter open field, edge bears same as road.

22.35 Spur, slopes SE.; desc. 5 ft. over NE. slope.

28.00 Ravine, drains SE.; asc. 55 ft. over SE. slope.

35.60 Top of ascent, slopes SE.; desc. 25 ft. over NE. slope.

40.02 Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

*FD. OK
B-91 D. BENTZ
MLP 1991-56*

T 26 S R 7 W
1/4
S 27 | S 26
1974

from which