

County Surveyor's Record, Douglas County, Oregon

15167

Dependent Resurvey, Portion of Subdivisional Lines.
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 10 ins. diam., bears N. 34° E., 78 1/2 lks. dist., mkd. 1/4 S26 BT..

An oak, 13 ins. diam., bears N. 35° W., 24 lks. dist., mkd. 1/4 S27 BT.

Descend 70 ft. over NE. slope.

40.15 Intersection of wire fences, extending E., W., and N.

48.00 Creek, 2 lks. wide, course N. 85° E.; asc. 50 ft. over SE. slope.

50.20 Wire fence, extends E. and W.

55.00 Top of ascent, slopes SE.; desc. 30 ft. over NE. slope.


58.70 Ravine, drains E.; asc. 55 ft. over SE. slope.

61.30 Spur, slopes S. 80° E.; desc. 20 ft. over NE. slope.

64.20 Ravine, drains S. 35° E.; asc. 30 ft. over S. slope.

68.10 Creek, 1 lk. wide, course S. 20° E.; asc. 210 ft. over SE. slope.

80.04 The cor. of secs. 22, 23, 26, and 27, perpetuated and recorded by the Douglas County Surveyor, in 1934, and further perpetuated and recorded by the County Surveyor, in 1966, monumented with an iron post, 1 1/4 ins. diam., firmly set, level with the ground, with brass cap mkd.



from which the remains of the original bearing trees

A decayed black oak stump, size indeterminate, bears S. 20° E., 36 lks. dist., with old axe marks visible on decayed blaze.

and bearing trees mkd. in 1934

A fir stump, 28 ins. diam., bears N. 62 1/2° E., 31 lks. dist., with scribe marks BT visible on decayed blaze.

A white oak, 13 ins. diam., bears N. 81 1/2° W., 165 lks. dist., with healed blaze.

and bearing trees mkd. in 1966

A black oak, 17 ins. diam., bears S. 7° E., 90 lks. dist., with healed blaze.

A cedar, 28 ins. diam., bears S. 22° E., 207 lks. dist., with healed blaze.

No other trees available within limits.

Add marks BLM 1974 to brass cap.

The corner is located on top of spur, slopes SE. , and at intersection of fences, extending N., S., E., and W.