

County Surveyor's Record, Douglas County, Oregon

15168

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Land, rolling hills.
Soil, rocky loam.
Timber, fir, cedar, oak, alder, maple, and hemlock;
undergrowth, salal, arrowwood, wild rose, manzanita,
poison oak, Oregon grape, and fern.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy.
of the Tp., perpetuated and recorded by the Douglas
County Surveyor, in 1960, with an iron post, 1 1/4 ins.
diam., and further perpetuated and recorded by the County
Surveyor, in 1964, monumented with an iron post, 1 1/4 ins.
diam., firmly set, projecting 8 ins. above ground, with
brass cap mkd.

T 26 S	R 7 W
S 33	S 34
S 4	S 3
T 27 S	
1964	

from which the remains of the original bearing trees

A white oak snag, 18 ins. diam., bears N. 47° W.,
80 lks. dist., with scribe marks BT visible on
open blaze.

and a bearing tree mkd. in 1960

A white oak, 10 ins. diam., bears N. 37 1/2° E., 196
lks. dist., with healed blaze.

and the remains of a bearing tree mkd. in 1964

A madrone root crown, size indeterminate, bears
S 48 1/2 ° E., 130 lks. dist.

No other trees available within limits.

During the 1964 perpetuation of this corner by the County
Surveyor, the iron post set in 1960 was found lying some
distance away. At this time the County Surveyor reset
the iron post alongside his own monument, with top mkd.
T26S T27S R7W S3 S4 S 33 S34 1960.

N. 0° 06' W., bet. secs. 33 and 34.

Ascend 50 ft. over SE. slope, through moderate timber
and heavy undergrowth, along a woven wire fence extending
N. and S.

3.50 Spur, slopes SE.; desc. 20 ft. over NE. slope.

5.80 Ravine, drains S. 35° E.; asc. 85 ft. over SE. slope.

17.00 Top of ascent, slopes SE.; desc. 5 ft. along E. slope.

20.15 Intersection of woven wire fences, extends E. and S.

20.40 Ravine, drains S. 20° E.; asc. 160 ft. over SE. slope.

39.98 Point for the 1/4 sec. cor. of secs. 33 and 34, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins.
in the ground, with brass cap mkd.