

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15170

CHAINS

From the cor. of secs. 26, 27, 34, and 35.

S. 89° 44' W., bet. secs. 27 and 34.

Descend 5 ft. over general W. slope, through scattering timber and moderate undergrowth.

5.00 Creek, 4 lks. wide, course S. 60° E.; asc. 195 ft. over NE. slope.

23.20 Spur, slopes N.; desc. 30 ft. over NW. slope.

38.25 Ravine, drains N. 30° E.; asc. 60 ft. over NE. slope.

39.95 Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 7 W
1/4 $\frac{S\ 27}{S\ 34}$
1974

*10.0K A-91
D. BEATZ MLP 1991-54*

from which

A fir, 11 ins. diam., bears N. 48 1/2° E., 69 lks. dist., mkd. 1/4 S27 BT.

A fir, 12 ins. diam., bears S. 57° E., 38 lks. dist., mkd. 1/4 S34 BT.

The corner is located in woven wire fence, extending N. and S.

Ascend 25 ft. over NE. slope.

46.65 Woven wire fence, extends N. 65° E. and S. 65° W.

46.70 Creek, 1 lk. wide, course N. 40° E.; asc. 270 ft. over NE. slope.

51.20 Enter open field, edge bears N. and S.

58.10 Gravelled road, 20 lks. wide, bears N. and S.

64.75 Woven wire fence, extends N. and S.

75.00 Top of ascent, slopes SW.; desc. 10 ft. over W. slope.

77.80 East edge of beaver pond, edge bears generally N. and S.; thence across pond.

79.90 True point for the cor. of secs. 27, 28, 33, and 34.

Land, rolling hills.

Soil, sandy loam.

Timber, fir, cedar, hemlock, alder, oak, and madrone; undergrowth arrowwood, wild rose, blackberry, poison oak, salal, Oregon grape, and fern.

N. 0° 08' W., bet. secs. 27 and 28.

Thence across beaver pond.