

County Surveyor's Record, Douglas County, Oregon

15171

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

- 1.40 N. edge of beaver pond, edge bears S. 40° E., and W.; desc. 5 ft. over NE. slope.
- 6.50 Creek, 1 lk. wide, course N. 75° E.; asc. 40 ft. over SE. slope.
- 14.70 Spur, slopes NE. ; desc. 70 ft. over NE. slope.
- 16.00 Woven wire fence, extends E. and W.
- 16.90 Creek, 2 lks. wide, course E.; asc. 115 ft. over SE. slope.
- 24.40 Spur, slopes E.; desc. 70 ft. over NE. slope.
- 27.30 Ravine, drains N. 85° E.; asc. 90 ft. over SE. slope.
- 37.50 Spur, slopes N. 75° E.; desc. 25 ft. over NE. slope.
- 39.98 Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26 S R 7 W
1/4
S 28 | S 27
1974

from which

A madrone, 15 ins. diam., bears S. 53 1/2° E., 75 lks. dist., mkd. 1/4 S27 BT.

A fir, 8 ins. diam., bears S. 83° W., 95 1/2 lks. dist., mkd. 1/4 S28 BT.

Descend 15 ft. over NE. slope.

- 45.40 Creek, 1 lk. wide, course N. 75° E.; asc. 190 ft. over SE. slope.
- 55.40 Top of rock bluff, 50 ft. high, faces S.; asc. 230 ft. over SE. slope.
- 59.97 Point for the N 1/16 sec. cor. of secs. 27 and 28.

Seat a brass tablet, 3 1/4 ins. diam., 3 1/2 ins stem, in drill hole, in solid rock, with top mkd.

N 1/16
S 28 | S 27
1974

from which

A fir, 6 ins. diam., bears N. 60 1/4° E., 50 lks. dist., mkd. N 1/16 S27 BT.

A fir, 7 ins. diam., bears N. 42 1/4° W., 73 lks. dist., mkd. N 1/16 S28 BT.

Ascend 235 ft. over SE. slope.

- 66.10 Spur, slopes E.; desc. 15 ft. over NE. slope.