

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15172

CHAINS
69.10

Ravine, drains S. 80° E.; asc. 10 ft. over SE. slope.

70.60

Top of rock bluff, 70 ft. high, faces N.; desc. 170 ft. over NE. slope.

72.50

Spur, slopes SE.; desc. 45 ft. over NE. slope.

76.10

Top of rock bluff, 55 ft. high, faces SW.; desc. 115 ft. over NE. slope.

79.96

The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 26 S R 7 W
S 21 | S 22
S 28 | S 27
1959

from which the remains of an original bearing tree

A decayed and burned fir stump, 20 ins. diam., bears S. 85° W., 26 lks. dist., with old axe marks visible on decayed face.

and new bearing trees

A fir, 6 ins. diam., bears N. 40 1/2° E., 22 lks. dist., mkd. T26S R7W S22 BT.

A fir, 8 ins. diam., bears S. 89 1/2° E., 10 1/2 lks. dist., mkd. T26S R7W S27 BT.

No other suitable trees available within limits.

Add marks 1974 to brass cap.

Land, mountainous.

Soil, rocky loam.

Timber, fir, cedar, hemlock, oak, alder, madrone, and cascara; undergrowth, ceanothus, manzanita, poison oak, huckleberry, gooseberry, wild rose, salal, Oregon grape, and fern.

From the cor. of secs. 22, 23, 26, and 27.

S. 89° 41' W., bet. secs. 22 and 27.

Ascend 250 ft. over general E. slope, along N. edge of open field, along a fence line extending W.

28.70

Spur, slopes SE.; desc. 5 ft. over gradual W. slope.

40.06

Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 7 W
1/4 S 22
S 27
1974

from which