

County Surveyor's Record, Douglas County, Oregon

15173

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 6 ins. diam., bears N. 23 1/2° E., 115 lks. dist., mkd. 1/4 S22 BT.</p> <p>A fir, 8 ins. diam., bears S. 11 1/2° E., 24 lks. dist., mkd. 1/4 S27 BT.</p> <p>A corner of woven wire fences extending E. and S., bears N. 40° W., 0.10 chs. dist.</p> <p>Descend 5 ft. over general W. slope.</p>
40.50	Spur, slopes S. 10° E., desc. 15 ft. over SW. slope.
44.25	Ravine, drains S. 50° E.; desc. 15 ft. over SW. slope.
48.50	Creek, 1 lks. wide, course S. 10° E.; asc. 170 ft. over general E. slope.
56.95	Spur, slopes SE.; desc. 30 ft. over SW. slope.
65.25	Creek, 1 lk. wide, course S. 55° E.; asc. 350 ft. over NE. slope.
80.12	<p>The cor. of secs. 21, 22, 27, and 28.</p> <p>Land, rolling hills. Soil, sandy loam. Timber, fir, oak, cedar, madrone, and alder; undergrowth manzanita, arrowwood, ceanothus, chinquapin, blackberry, poison oak, and fern.</p>
	<p>N. 0° 08' W., bet. secs. 21 and 22.</p> <p>Descend 110 ft. over NE. slope, through scattering timber and heavy undergrowth.</p>
7.50	Ravine, drains S. 65° E.; asc. 35 ft. over SE. slope.
9.40	Top of ascent, slopes S. 80° E.; desc. 20 ft. over NE. slope.
11.10	Ravine, drains N. 75° E.; asc. 20 ft. over SE. slope.
12.85	Top of ascent, slopes N. 85° E.; desc. 45 ft. over NE. slope.
14.90	Ravine, drains S. 60° E.; asc. 55 ft. over SE. slope.
16.85	Top of ascent, slopes E.; desc. 5 ft. over NE. slope.
20.025	<p>Point for the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S 1/16 S 21 S 22 1974</p> </div> <p>from which</p> <p>A fir, 10 ins. diam., bears S. 85° E., 15 lks. dist., mkd. S 1/16 S22 BT.</p> <p>A fir, 9 ins. diam., bears N. 87° W., 10 lks. dist., mkd. S 1/16 S21 BT.</p>