

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15174

CHAINS

Descend 160 ft. over broken NE. slope.

40.05

Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 7 W
1/4
S 21 | S 22
1974

from which

A fir, 8 ins. diam., bears S. 32° E., 86 lks. dist., mkd. 1/4 S22 BT.

A fir, 9 ins. diam., bears S. 40° W., 95 1/2 lks. dist., mkd. 1/4 S21 BT.

The corner is located at bottom of descent, slopes S. 75° E.

Ascend 10 ft. over SE. slope.

43.00

Top of ascent, slopes E.; desc. 140 ft. over NE. slope.

50.00

Creek, 2 lks. wide, course N. 40° W.; asc. 65 ft. over SW. slope.

55.20

Top of ascent, slopes S. 80° W.; desc. 20 ft. over NW. slope.

56.75

Bottom of descent, slopes S. 50° W.; asc. 15 ft. over SE. slope.

58.15

Top of ascent, slopes NW. ; desc. 290 ft. over NE. slope.

70.85

Abandoned dirt road, 10 lks. wide, bears E. and W.

75.35

Creek, 3 lks. wide, course N. 50° E.; asc. 85 ft. over SE. slope.

80.10

The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 26 S R 7 W
S 16 | S 15
S 21 | S 22
1959

from which a bearing tree described by Zirpel and Martin, in 1959

A fir, 36 ins. diam., bears N. 18° E.; 70 lks. dist., with scribe marks T26S R7W S15 CS BT visible on open blaze.

and a new bearing tree

A fir, 6 ins. diam., bears S. 21° W., 30 lks. dist., mkd. T26S R7W S21 BT.