

# County Surveyor's Record, Douglas County, Oregon

**15175**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A hemlock, 8 ins. diam., bears N. 54° W., 14 lks.  
dist., mkd. T26S R7W S16 BT.

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, cedar, hemlock, madrone, and oak; under-  
growth, manzanita, salal, poison oak, arrowwood, ceano-  
thus, and fern.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy.  
of the Tp.

N. 0° 19' E., bet. secs. 32 and 33.

Ascend 55 ft. over SE. slope, through scattering timber  
and light undergrowth.

7.50 Bear Ridge, divides Hubbard Creek and Umpqua River  
drainage, bears N. 10° E., and SW.; desc. 25 ft. over  
general NW. slope.

15.00 Callahan Road, paved 50 lks. wide, bears S. 15° E.  
and N. 50° W., in curve.

20.145 Point for the S 1/16 sec. cor. of secs. 32 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ina.  
in the ground, with brass cap mkd.

S 1/16  
S 32 | S 33  
1974

from which

A fir, 7 ins. diam., bears N. 40° E., 24 lks.  
dist., mkd. S 1/16 S33 BT.

A fir, 20 ins. diam., bears S. 44° W., 107 lks.  
dist., mkd. S 1/16 S32 BT.

Descend 155 ft. over NW. slope.

20.55 Dirt road, 15 lks. wide, bears N. 35° E. and S. 35° W.

35.70 Ravine, drains N. 70° W.; desc. 10 ft. over NW. slope.

40.29 Point for the 1/4 sec. cor. of secs. 32 and 33, at propor-  
tionate distance; there is no remaining evidence of the  
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 26 S R 7 W  
1/4  
S 32 | S 33  
1974

from which

A fir, 6 ins. diam., bears S. 32° E., 29 lks.  
dist., mkd. 1/4 S33 BT.

A fir, 13 ins. diam., bears S. 70 1/4° W., 59 lks.  
dist., mkd. 1/4 S32 BT.