

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15176

**CHAINS**

The corner is located at bottom of descent, slopes  
N. 40° W.

Ascend 25 ft. over SW. slope.

46.80 Spur, slopes N. 50° W., desc. 285 ft. over NW. slope.

65.00 Creek, 1 lk. wide, course N. 70° W., asc. 340 ft. over  
SW. slope.

80.58 Point for the cor. of secs. 28, 29, 32, and 33, at pro-  
portionate distance; there is no remaining evidence of  
the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 26 S R 7 W
S 29   S 28
S 32   S 33
1974

from which

A madrone, 6 ins. diam., bears N. 69° E., 97 lks.  
dist., mkd. T26S R7W S28 BT.

A fir, 10 ins. diam., bears S. 5° E., 160 lks.  
dist., mkd. T26S R7W S33 BT.

A fir, 12 ins. diam., bears S. 32° W., 88 lks.  
dist., mkd. T26S R7W S32 BT.

A fir, 9 ins. diam., bears N. 40 1/2° W., 129 lks.  
dist., mkd. T26S R7W S29 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, alder, and pine; undergrowth,  
manzanita, arrowwood, ceanothus, poison oak, willow,  
blackberry, wild rose, salal, Oregon grape, and fern

From the true point for the cor. of secs. 27, 28, 33, and 34.

S. 89° 40' W., bet. secs. 28 and 33.

Thence across beaver pond.

0.50 W. edge of beaver pond, edge bears N. 30° W. and  
S. 30° E.; asc. 1 ft. over general NE. slope.

0.63 Point selected for the witness corner of secs. 27, 28,  
33, and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins.  
in the ground, with brass cap mkd.

W C
T 26 S R 7 W
S 28   S 27
S 33   S 34
1974

from which