

# County Surveyor's Record, Douglas County, Oregon

**15177**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A madrone, 6 ins. diam., bears N. 3° E., 48 lks.  
dist., mkd. X BT.

No other suitable trees available within limits.

Ascend 1 ft. over general NE. slope.

0.70

Intersect the W. bdy. of the Josiah Atterbury Donation  
Land Claim No. 47.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins.  
in the ground, with brass cap mkd.

T 26 S R 7 W  
S 28 | C  
S 33 | 47  
1974

from which

A madrone, 8 ins. diam., bears S. 67 1/2° W., 106  
lks. dist., mkd. T26S R7W S33 BT.

A madrone, 10 ins. diam., bears N. 56 1/2° W., 144  
lks. dist., mkd. T26S R7W S28 BT.

From this point, the NW. cor. of Donation Land Claim  
No. 47, bears N. 0° 01' W., 10.20 chs. dist., herein-  
after described.

Ascend 25 ft. over general NE. slope.

4.09

Intersect the remains of the original line tree; a root  
hole, with a down cedar alongside, 36 ins. diam., mkd.  
with 4 notches on E. and W. sides. This now functions  
as an angle point on line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

A P  
T 26 S R 7 W  
S 28  
S 33  
1974

S 89° 40' W., beginning new measurement.

Ascend 200 ft. over general NE. slope.

14.50

Ravine, drains N. 50° E.; asc. 35 ft. over NE. slope.

15.735

Point for the E 1/16 sec. cor. of secs. 28 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.  
in the ground, with brass cap mkd.

E 1/16 S 28  
S 33  
1974

from which

A fir, 6 ins. diam., bears N. 44 1/2° E., 56 lks.  
dist., mkd. E 1/16 S28 BT.

A fir, 5 ins. diam., bears S. 68° W., 71 lks.  
dist., mkd. E 1/16 S33 BT.