

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon.

15178

CHAINS	
	Ascend 210 ft. over general E. slope.
31.50	Rock bluff, 90 ft. high, faces E.; asc. 125 ft. over E. slope.
35.56	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 26 S R 7 W 1/4 $\frac{S\ 28}{S\ 33}$ 1974
	from which
	A fir, 8 ins. diam., bears N. 76° E., 48 lks. dist., mkd. 1/4 S28 BT.
	A fir, 6 ins. diam., bears S. 17 1/2° W., 6 1/2 lks. dist., mkd. 1/4 S33 BT.
	Ascend 400 ft. over broken E. slope.
46.50	Rock bluff, 110 ft. high, faces E.; asc. 150 ft. over E. slope.
51.20	Bear Ridge, divides Hubbard Creek, and Umpqua River drainage, bears N. 10° E. and S. 10° W., desc. 140 ft. over SW. slope.
54.15	Dirt road, 25 lks. wide, bears N. 10° E. and S. 10° W.
75.21	The cor. of secs. 28, 29, 32, and 33.  Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, madrone, alder, and chinquapin; undergrowth, ceanothus, vine maple, arrowwood, manzanita, willow, poison oak, blackberry, wild rose, salal, and fern.
	N. 0° 16' E., bet. secs. 28 and 29.  Descend 70 ft. over NW. slope, through scattering timber and moderate undergrowth.
33.85	Dirt road, 15 lks. wide, bears N. and S. 40° E., thence along road.
37.85	Leave dirt road, bears N. 60° W., and S.
40.29	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 26 S R 7 W 1/4 S 29   S 28 1974