

County Surveyor's Record, Douglas County, Oregon

15179

Dependent Resurvey, Portion of Subdivisional lines.
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 7 ins. diam., bears S. 30 3/4° E., 14 lks
dist., mkd. 1/4 S28 BT.

A fir, 6 ins. diam., bears N. 74 1/2° W., 23 lks.
dist., mkd. 1/4 S29 BT.

Descend 585 ft. over NE. slope.

73.10 Creek, 3 lks. wide, course W.; asc. 225 ft. over SW.
slope.

79.90 Rock bluff, 15 ft. high, faces S.; asc. 15 ft. over SW.
slope.

80.58 The cor. of secs. 20, 21, 28, and 29, monumented with an
iron post, 2 1/2 ins. diam., firmly set in a mound of stone,
3 ft. base, 1 1/2 ft. high, with brass cap mkd.

T 26 S R 7 W
S 20 | S 21
S 29 | S 28
1959

from which a bearing object mkd. by Zirpel and Martin,
in 1959

A bedrock outcropping, chiseled X B0, bears
S. 70° E., 11 1/2 lks. dist.

and a new bearing tree

A madrone, 8 ins. diam., bears S. 39° W., 11 lks.
dist., mkd. T26S R7W S29 BT.

No other suitable trees available within limits.

Land, mountainous.

Soil, rocky loam.

Timber, fir, hemlock, cedar, alder, amdrone, and chin-
quapin; undergrowth, manzanita, vine maple, arrowwood,
salal, Oregon grape, willow wild rose, poison oak, and
fern.

From the cor. of secs. 15, 16, 21, and 22.

N. 89° 30' W., bet. secs. 16 and 21.

Ascend 485 ft. over SE. slope, through scattering timber
and heavy undergrowth.

19.55 Point for the E 1/16 sec. cor. of secs. 16 and 21,
occupied by a fir, 20 ins. diam., mkd. E 1/16 S16 on N.
face, and S21 on S. face.

from which

A fir, 22 ins. diam., bears N. 9° E., 54 lks.
dist, mkd. E 1/16 S16 BT.

A fir, 19 ins. diam., bears S. 83° E., 45 lks.
dist., mkd. E 1/16 S21 BT.