

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15180

CHAINS

An iron post, 28 ins. long, 2 1/2 ins. diam., set 20 ins. in the ground, for a reference monument, bears S. 83° E., 30 lks. dist., with brass cap mkd. E 1/16 S21 RM 1974, and an arrow pointing to the corner.

Ascend 170 ft. over SE. slope.

23.70 Bear Ridge, divides Hubbard Creek, and Umpqua River drainage, bears N. 10° E., and S. 20° W.; desc. 240 ft. over NW. slope.

23.90 Dirt road, 15 lks. wide, bears N. and S.

31.90 Ravine, drains N. 40° W.; asc. 60 ft. over broken N. slope.

39.10 Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins diam., 24 ins. in the ground, with brass cap mkd.

T 26 S R 7 W
1/4 $\frac{S\ 16}{S\ 21}$
1974

from which

A white fir, 21 ins. diam., bears N. 51° E., 97 lks. dist., mkd. 1/4 S16 BT.

A fir, 19 ins. diam., bears S. 39° W., 67 lks. dist., mkd. 1/4 S21 BT.

Descend 90 ft. over NW. slope.

47.70 Spur, slopes NW.; desc. 145 ft. over NW. slope.

50.90 Camp Creek, 2 lks. wide, course N. 25° W.; asc. 120 ft. over NE. slope.

54.20 Spur, slopes N.; desc. 30 ft. over NW. slope.

56.90 Ravine, drains N.; asc. 100 ft. over NE. slope.

61.40 Top of ascent, slopes N.; desc. 15 ft. over NW. slope.

63.70 Ravine, drains N. 30° E., asc. 70 ft. over NE. slope.

67.50 Top of ascent, slopes N.; desc. 125 ft. over NW. slope.

71.50 Creek, 1 lk. wide, course N. 15° W.; asc. 225 ft. over NE. slope.

78.20 The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 26 S R 7 W
 $\frac{S\ 17\ | S\ 16}{S\ 20\ | S\ 21}$
1959

from which the remains of the original bearing trees