

County Surveyor's Record, Douglas County, Oregon

15181

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears N. 10° E., 16 lks. dist., with a down fir alongside, 25 ins. diam., with healed blaze. (Record, N. 16° E.)

and the remains of the bearing trees mkd. by Zirpel and Martin, in 1959

A fir snag, 11 ins. diam., bears S. 16 1/4° E., 120 1/2 lks. dist., with scribe marks T26S R7W S21 BT visible on open blaze.

A fir, 17 ins. diam., bears S. 71 3/4° W., 135 lks. dist., with scribe marks T26S R7W S20 BT visible on open blaze. (Record, 133 lks.)

A root hole, bears N. 13 1/4° W., 91 lks. dist., with a down fir alongside, 11 ins. diam., with scribe marks T26S R7W S17 BT visible on open blaze.

and bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1966

A fir, 18 ins. diam., bears S. 51° E., 108 lks. dist., with fragmentary scribe marks visible on open double blaze.

A fir, 19 ins. diam., bears N. 5° W., 167 lks. dist., with fragmentary scribe marks visible on open double blaze.

and a new bearing tree

A fir, 8 ins. diam., bears N. 60° E., 67 lks. dist., mkd. T26S R7W S16 BT.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, cedar, hemlock, madrone, and pine; undergrowth, manzanita, salal, poison oak, arrowwood, huckleberry, and ceanothus.

From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp.

N. 0° 36' E., bet. secs. 31 and 32.

Descend 155 ft. over NE. slope, through moderate timber and undergrowth.

8.50 Creek, 1 lk. wide, course N. 75° E.; asc. 250 ft. over SE. slope.

19.00 Spur, slopes S. 30° E.; continue ascent 415 ft. over SE. slope.

39.91 Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 26S R 7 W
1/4
S 31 | S 32
1974