

County Surveyor's Record, Douglas County, Oregon

15183

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon.

CHAINS 40.02	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W 1/4 $\frac{S\ 29}{S\ 32}$ 1974</p> <p>from which</p> <p style="padding-left: 40px;">A white fir, 14 ins. diam., bears N. 76° E., 46 lks. dist., mkd. 1/4 S29 BT.</p> <p style="padding-left: 40px;">A white fir, 10 ins. diam., bears S. 74 1/2° E., 54 lks. dist., mkd. 1/4 S32 BT.</p> <p>Ascend 30 ft. over NE. slope.</p>
43.40	Dirt road, 20 lks. wide, bears N. 5° W. and S. 5° E.
48.20	Spur, slopes NE.; desc. 5 ft. over W. slope.
51.10	Bottom of descent, slopes N.; asc. 140 ft. over E. slope.
54.20	Rock bluff, 20 ft. high, faces E.; asc. 25 ft. over E. slope.
56.10	Spur, slopes N.; desc. 60 ft. over NW. slope.
60.20	Bottom of descent, slopes N.; asc. 20 ft. over NE. slope.
61.90	Spur, slopes N.; desc. 30 ft. over NW. slope.
65.85	Ravine, drains N. 10° W., asc. 15 ft. over NE. slope.
67.40	Spur, slopes N. 10° W.; desc. 85 ft. over broken W. slope.
80.04	<p>The cor. of secs. 29, 30, 31, and 32.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, alder, madrone, chinquapin, and yew; undergrowth, vine maple, hazel, arrowwood, salal, Oregon grape, willow, poison oak, manzanita, and fern.</p> <hr style="border: 0.5px solid black;"/> <p>N. 89° 45' W., bet. secs. 30 and 31.</p> <p>Descend 20 ft. over NW. slope, through scattering timber and moderate undergrowth.</p>
4.35	Creek, 1 lk. wide, course N. 35° W.; asc. 30 ft. over NE. slope.
5.75	Top of ascent, slopes N.; desc. 35 ft. over NW. slope.
9.60	Creek, 3 lks. wide, course N. 10° E.; asc. 85 ft. over NE. slope.