

# County Surveyor's Record, Douglas County, Oregon

15185

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A root hole, bears N. 64° E., 15 lks. dist., with a down fir alongside, size indeterminate, no marks visible.

A decayed and burned fir stump, size indeterminate, bears S. 22° W., 21 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Zirpel and Martin, in 1959

A fir, 18 ins. diam., bears N. 12° E., 40 lks. dist., with scribe marks T26S R7W S30 BT visible on open blaze. (Record, N. 14° E.)

A fir, 10 ins. diam., bears S. 18 1/2° E., 215 lks. dist., with healed blaze. (Record, S. 16° E.)

A fir, 10 ins. diam., bears S. 9° W., 197 lks. dist., with healed blaze. (Record, S. 11° W.)

A root hole, bears N. 83° W., 20 lks. dist., with a down fir alongside, 28 ins. diam., with scribe marks T26S R8W S25 visible on open blaze.

and bearing trees described by Zirpel and Martin, in 1959

A fir, 27 ins. diam., bears N. 19° E., 48 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 43° W., 48 lks. dist., with scribe mark V visible on opened blaze.

and a bearing tree mkd. by Bruce Shaner, Registered Land Surveyor No. 430, in 1973

A fir, 10 ins. diam., bears N. 48 1/2° W., 160 lks. dist., with scribe marks T26S R8W S25 visible on open blaze.

Land, mountainous.

Soil, rocky clay

Timber, fir, hemlock, cedar, alder, chinquapin, and madrone; undergrowth, vine maple, hazel, arrowwood, huckleberry, poison oak, salal Oregon grape, blackberry, ceanothus, and fern.

From the cor. of secs. 29, 30, 31, and 32.

N. 0° 54' E., bet. secs. 29 and 30.

Descend 240 ft. over NW. slope. through moderate timber and undergrowth.

16.45 Creek, 4 lks. wide, course N. 70° E.; asc. 410 ft. over SE. slope.

33.20 Spur, slopes S. 80° E.; desc. 50 ft. over NE. slope.

39.91 The 1/4 sec. cor. of secs. 29 and 30, perpetuated and recorded by the Douglas County Surveyor, in 1959, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.