

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon.

15186

CHAINS

C S  
T 26 S R 7 W  
1/4 S 30 | S 29  
1959

from which the remains of the original bearing trees

A fir snag, 10 ins. diam., bears N. 20° E., 13 lks.  
dist., no marks visible.

A fir snag, 22 ins. diam., bears N. 30° W., 13 lks.  
dist., with fragmentary scribe marks visible on  
bark blaze.

and the remains of bearing trees mkd. by the County  
Surveyor

A fir snag, 14 ins. diam., bears N. 27° E., 90 lks.  
dist., with scribe marks BT visible on open blaze.

A root hole, bears S. 33° W., 14 lks. dist., with a  
down fir alongside, 10 ins. diam., with scribe  
marks 1/4 S30 CS BT visible on decayed blaze.

and new bearing trees

A fir, 6 ins. diam., bears N. 28 1/2° E., 35 1/2 lks.  
dist., mkd. 1/4 S29 BT.

A fir, 6 ins. diam., bears S. 54° W., 16 lks.  
dist., mkd. 1/4 S30 BT.

Add marks BLM 1974 to brass cap.

---

N. 0° 06' E., beginning new measurement.

Descend 265 ft. over NE. slope. through scattering  
timber and moderate undergrowth.

32.45 Ravine, drains N. 25° E.; asc. 5 ft. over SE. slope.

34.30 Spur, slopes N. 20° E.; desc. 30 ft. over NE. slope.

40.11 Point for the cor. of secs. 19, 20, 29, and 30, at pro-  
portionate distance; there is no remaining evidence of  
the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, brass cap mkd.

T 26 S R 7 W  
S 19 | S20  
S 30 | S 29  
1974

from which

A fir, 6 ins. diam., bears N. 63 1/2° E., 45 lks.  
dist., mkd. T26S R7W S20 BT.

A fir, 6 ins. diam., bears S. 21° E., 35 lks.  
dist., mkd. T26S R7W S29 BT.

A fir, 6 ins. diam., bears S. 53° W., 16 lks.  
dist., mkd. T26S R7W S30 BT.