

County Surveyor's Record, Douglas County, Oregon

15187

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A fir, 6 ins. diam., bears N. 35 1/2° W., 15 lks. dist., mkd. T26S. R7W S19 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, alder, madrone, and pine; undergrowth, vine maple, hazel, arrowwood, salal, Oregon grape, manzanita, ceanothus, willow, huckleberry, and fern.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>S. 88° 47' W., bet. secs. 20 and 29.</p> <p>Descend 415 ft. over SW. slope, through light timber and heavy reproduction.</p>
18.55	Creek, 2 lks. wide, course N. 50° W.; asc. 125 ft. over NE. slope.
26.90	Spur, slopes N.; desc. 155 ft. over NW. slope.
30.15	Creek, 1 lk. wide, course N. 5° W.; asc. 250 ft. over NE. slope.
37.90	Abandoned dirt road, 10 lks. wide, bears N. 50° W. and S. 50° E.
39.95	Point for the 1/4 sec. cor. of secs. 20 and 29, at propor- tionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="margin-left: 100px;">T 26 S R 7 W 1/4 S 20 S 29 1974</p>
	from which
	<p>A fir, 6 ins. diam., bears N. 42° W., 25 1/2 lks. dist., mkd. 1/4 S20 BT.</p> <p>A fir, 6 ins. diam., bears S. 65° W., 18 lks. dist., mkd. 1/4 S29 BT.</p>
	Ascend 5 ft. over NE. slope.
45.05	Spur, slopes N. 10° W.; asc. 25 ft. over NE. slope.
45.90	Ravine, drains N. 20° E.; asc. 10 ft. over NE. slope.
48.40	Spur, slopes N.15° W.; desc. 315 ft. over NW. slope.
58.20	Abandoned dirt road, 10 lks. wide, bears N. 30° E. and S. 30° W.
61.90	Same abandoned dirt road, bears N. 30° W. and S. 30° E., also top of spur, slopes NW. ; desc. 110 ft. over NW. slope.
64.60	Hubbard Creek, Road, gravelled, 15 lks. wide, bears N. 20° E., and S.