

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon.

15188

CHAINS

- 66.20 Hubbard Creek, 10 lks. wide, course N. 10° E.; asc. 255 ft. over E. slope.
- 66.50 Top of rock bluff, 100 ft. high, faces E.; asc. 100 ft. over NE. slope.
- 73.45 Spur, slopes N. 10° E.; desc. 85 ft. over NW. slope.
- 77.60 Creek, 2 lks. wide, course N. 10° E.; asc. 50 ft. over NE. slope.
- 79.90 The cor. of secs. 19, 20, 29, and 30.

Land, mountainous.
Soil, rocky clay and loam.
Timber, fir, cedar, hemlock, pine, madrone, and chin-
quapin; undergrowth, vine maple, hazel, arrowwood, man-
zanita, salal, Oregon grape, poison oak, huckleberry,
ceanothus, and fern.

N. 89° 28' W., bet. secs. 19 and 30.

Ascend 150 ft. over NE. slope, through moderate timber
and undergrowth.

- 15.35 Top of ascent, slopes N. 20° E.; desc. 25 ft. over NW. slope.
- 20.45 Dirt road, 10 lks. wide, at bottom of descent, bears N. 40° W., and S. 40° E.; asc. 30 ft. over NE. slope.
- 27.40 Top of ascent, slopes N.; desc. 35 ft. over NW. slope.
- 32.90 Dirt road, 15 lks. wide, at bottom of descent, bears NE. and SW.; asc. 60 ft. over E. slope.
- 38.90 Top of ascent, slopes N.; desc. 5 ft. over NW. slope.
- 39.80 Point for the 1/4 sec. cor. of secs. 19 and 30, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 26 S R 7 W

1/4 $\frac{S\ 19}{S\ 30}$

1974

from which

A fir, 6 ins. diam., bears N. 44° E., 29 1/2 lks.
dist., mkd. 1/4 S19 BT.

A fir, 8 ins. diam., bears S. 67° W., 36 1/2 lks.
dist., mkd. 1/4 S30 BT.

Descend 45 ft. over NW. slope.

- 44.50 Bottom of descent, slopes S.; asc. 40 ft. over SE. slope.
- 47.60 Top of ascent, slopes S.; desc. 240 ft. over SW. slope.
- 57.75 Rock bluff, 40 ft. high, faces S. 40° W.; desc. 40 ft. over SW. slope.