

County Surveyor's Record, Douglas County, Oregon

15190

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

CHAINS
40.11

The 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 26 S R 7 W
1/4
S 19 | S 20
1969

form which the remains of the original bearing trees

A sawed fir stump, 60 ins. diam., bears S. 69° E.,
50 lks. dist., no marks visible.

A sawed fir stump, 48 ins. diam., bears N. 23° W.,
32 lks. dist., no marks visible.

and bearing trees mkd. by Roseberry, in 1969

A fir 5 ins. diam., bears N. 49° E., 29 1/2 lks.
dist., with scribe marks X BT visible on open
blaze.

A fir, 7 ins. diam., bears N. 55° W., 43 lks.
dist., with scribe marks 1/4 S19 BT visible on
open blaze.

Add marks 1974 to brass cap.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, cascara, madrone, alder,
yew, maple, and chinquapin; undergrowth, vine maple,
hazel, arrowwood, huckleberry, blackberry, salmonberry,
ceanothus, poison oak, Oregon grape, salal, and fern.

From the cor. of secs. 5, 6, 7, and 8, perpetuated and
recorded by the County Surveyor, in 1966, monumented
with an iron post, 2 ins. diam., firmly set, projecting
8 ins. above ground, with brass cap mkd.

T 26 S
S 6 | S 5
S 7 | S 8
R 7 W
1966

from which the remains of the original bearing trees

A fir stump, 35 ins. diam., bears N. 17° E., 66
lks. dist., no marks visible. (Record, N. 20° E.,)

A fir, 25 ins. diam., bears S. 85° E., 18 lks.
dist., with scribe marks S8 visible on opened
blaze.

A fir stump, 36 ins. diam., bears S. 80° W., 14 lks.
dist., no marks visible.

A fir snag, 35 ins. diam., bears N. 20° W., 85
lks. dist., with healed blaze.

and a bearing tree of no record

A fir, 18 ins. diam., bears S. 65° E., 54 lks.
dist., with healed blaze.