

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 7 W., Willamette Meridian, Oregon

15192

CHAINS

82.66

The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., re-established under Group No. 739, concurrently with this resurvey, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 26 S
R 8 W R 7 W
S 1 | S 6
S 12 | S 7
1971

from which

A madrone, 4 ins. diam., bears S. 83° E., 26 lks. dist., mkd. X BT.

A fir, 15 ins. diam., bears S. 5° E., 29 lks. dist., mkd. T26S R7W S7 BT.

A fir, 23 ins. diam., bears S. 39° W., 74 lks. dist., mkd. T26S R8W S12 BT.

No suitable tree available in sec. 6.

Land, mountainous.

Soil, sandy, clay loam.

Timber, fir, hemlock, cedar, madrone, alder, maple, and chinquapin; undergrowth, vine maple, salal, fern, ceanothus, rhododendron, and poison oak.

From the cor. of secs. 5, 6, 7, and 8.

N. 1° 54' W., bet. secs. 5 and 6.

Descend 480 ft. over NW. slope, through heavy timber and dense undergrowth.

23.35

Dirt road, 10 lks. wide, bears N. 40° E. and S. 40° W.

40.34

Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

1/4
S 6 | S 5
T 26 S | R 7 W
1971

from which

A fir, 17 ins. diam., bears N. 5° E., 23 lks. dist., mkd. 1/4 S5 BT.

A fir, 42 ins. diam., bears N. 39 1/4° W., 71 lks. dist., mkd. 1/4 S6 BT.

Descend 750 ft. along N. slope.

62.00

Creek, 5 lks. wide, course N. 70° W.; asc. 155 ft. over SW. slope.