

County Surveyor's Record, Douglas County, Oregon

15198

Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 8 W., Willamette Meridian, Oregon.

CHAINS

T 26 S
R 8 W R 7 W
1/4
S 24 | S 19
1959

from which the remains of the original bearing trees

A sawed fir stump, 31 ins. diam., bears N. 8 3/4° E.,
58 lks. dist., with illegible scribe marks
visible on partially opened blaze.

A burned and decayed fir snag, 36 ins. diam., bears
N. 29° W., 15 lks. dist., with scribe marks BT
in negative on overgrowth, and scribe mark B
found in the center of decayed trunk.

and new bearing trees

A fir, 6 ins. diam., bears N. 43° E., 56 lks.
dist., mkd. 1/4 S19 BT.

A fir, 6 ins. diam., bears N. 49 1/2° W., 34 1/2 lks.
dist., mkd. 1/4 S24 BT.

N. 0° 14' W., bet. secs. 19 and 24, marking and blazing
the true line.

Descend 205 ft. over NE. slope, through heavy reproduc-
tion and dense undergrowth.

14.20 Creek, 4 lks. wide, course N. 20° E.; asc. 75 ft. over
SE. slope.

16.05 Spur, slopes E.; desc. 340 ft. over NE. slope.

22.30 Hubbard Creek Road, 25 lks. wide, bears N. 45° W. and
S. 45° E.

29.45 Creek, 1 lk. wide, course E.; desc. 5 ft. over NE.
slope.

30.75 Creek, 5 lks. wide, course E.; asc. 30 ft. over SE.
slope.

33.05 Hubbard Creek, Road, 25 lks. wide, bears N. 10° E. and
W., also spur, slopes SE.; desc. 15 ft. along E. slope.

40.20 The cor. of secs. 13, 18, 19, and 24, on the E. bdy. of
the Tp., perpetuated and recorded by Richard C. Grant,
Registered Engineer No. 2807, in 1958, from testimony
of longtime local citizens, and subsequently perpetuated
by Lynn M. Roseberry, during a 1969 dependent resurvey,
monumented with an iron post, 1 in. diam., firmly set,
protruding 12 ins. above ground, with brass cap mkd.

T26S R8W
S 13 | S 18
S 24 | S 19
BLM
1969
T26S R7W

from which bearing trees mkd. by Roseberry

A fir, 6 ins. diam., bears N. 81 1/2° E., 36 lks.
dist., with healed double blaze.