

County Surveyor's Record, Douglas County, Oregon

15199

Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 8 W., Willamette Meridian, Oregon.

CHAINS

A fir, 8 ins. diam., bears S. 86 1/2° E., 200 lks. dist., with healed blaze.

A fir, 6 ins. diam., bears S. 11° W., 8 1/2 lks. dist., with healed double blaze.

A fir, 6 ins. diam., bears N. 81° W., 37 lks. dist., with healed double blaze.

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, cedar, maple, tan oak, chinquapin; undergrowth, salal, rhododendron, hazel, fern, poison oak, and vine maple.

N. 0° 12' W., bet. secs. 13 and 18.

Ascend 165 ft. over SE. slope. through scattering timber and dense undergrowth.

- 9.70 Spur, slopes N. 70° E.; desc. 15 ft. over NE. slope.
- 11.80 Ravine, drains N. 80° E.; desc. 100 ft. over SE. slope.
- 15.60 Spur, slopes N. 80° E.; desc. 170 ft. over NE. slope.
- 19.80 Dry creek, 3 lks. wide, drains E.; asc. 375 ft. over SE. slope.
- 31.30 Spur, slopes N. 75° E.; desc. 390 ft. over NE. slope.
- 40.39 Point for the 1/4 sec. cor. of secs. 13 and 18, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

1/4
S 13 | S 18
T. 26 S
R 8 W R 7 W
1971

Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, W. of corner.

There are no suitable bearing trees within limits.

N. 0° 10' W., beginning new measurement.

Descend 85 ft. over NE. slope.

- 1.05 Creek, 10 lks. wide, course E.; asc. 215 ft. over SE. slope.
- 5.60 Spur, slopes N. 55° E.; desc. 90 ft. over along E. slope.
- 12.85 Ravine, drains N. 35° E.; asc. 25 ft. over SE. slope.
- 16.05 Spur, slopes S. 65° E.; desc. 15 ft. over NE. slope.
- 17.35 Ravine, drains S. 60° E.; asc. 10 ft. over SE. slope.