

# County Surveyor's Record, Douglas County, Oregon

15200

Dependent Resurvey of a Portion of the East Boundary  
T. 26 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

- 18.60 Spur, slopes S. 85° E.; desc. 80 ft. over NE. slope.
- 21.40 Dry creek, 5 lks. wide, drains S. 70° E.; asc. 255 ft. over SE. slope.
- 26.70 Spur, slopes N. 85° E.; desc. 140 ft. over NE. slope.
- 31.35 Creek, 1 lk. wide, course N. 85° E.; asc. 270 ft. over SE. slope.
- 37.70 Spur, slopes N. 65° E.; desc. 80 ft. over NE. slope.
- 40.31 Ravine, drains S. 85° E.; asc. 5 ft. over SE. slope.
- 40.45 True point for the cor. of secs. 7, 12, 13, and 18, falls on rock outcropping, 40 ft. high, slopes E.; determined by the method of irregular boundaries; there is no remaining evidence of the original corner.

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, hemlock, madrone, cedar, maple, tan oak, and chinquapin; undergrowth, salal, rhododendron, hazel, fern, poison oak, and vine maple.


N. 0° 07' W., bet. secs. 7 and 12.

Ascend 5 ft. over SE. slope.

*50*  
~~0.05~~  
*9/12/82*  
*2/18*

Point selected for the witness sec. cor. of secs. 7, 12, 13, and 18.

Set a brass tablet, 3 ins. diam., 3 1/2 ins. stem, in a drill hole, in solid rock, mkd.



from which

A madrone, 5 ins. diam., bears N. 84 1/2° E. 68 lks. dist., mkd. X BT.

A madrone, 4 ins. diam., bears S. 61 1/2° W., 90 lks. dist. mkd. X BT.

A fir, 20 ins. diam., bears N. 44° W., 125 lks. dist., mkd. X BT.

No other tree available within limits.

The witness corner is located at top of ascent, slopes S. 60° E.

Descend 85 ft. over NE. slope, through scattering timber and light undergrowth.

- 3.60 Ravine, drains E.; asc. 70 ft. over SE. slope.

- 5.20 spur, slopes S. 85° E.; desc. 10 ft. over NE. slope.