

County Surveyor's Record, Douglas County, Oregon

15201

Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 7 W., Willamette Meridian, Oregon.

CHAINS	
5.85	Ravine, drains S. 80° E.; asc. 45 ft. over SE. slope.
6.95	Spur, slopes S. 75° E.; desc. 15 ft. over NE. slope.
8.05	Ravine, drains S. 80° E.; asc. 95 ft. over SE. slope.
17.30	Spur, slopes S. 80° E.; desc. 15 ft. over NE. slope.
20.13	Point for the S 1/16 sec. cor. of secs. 7 and 12. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> S 1/16 S 12 S 7 1971 </div> from which <div style="margin-left: 40px;"> A chinquapin, 6 ins. diam., bears N. 58° E., 12 lks. dist., mkd. S 1/16 S7 BT. A madrone, 8 ins. diam., bears S. 9° W., 17 lks. dist., mkd. S 1/16 S12 BT. </div> Descend 535 ft. over NE. slope.
40.26	Point for the 1/4 sec. cor. of secs. 7 and 12, determined by the method of irregular boundaries; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. <div style="text-align: center;"> 1/4 S 12 S 7 T 26 S R 8 W R 7 W 1971 </div> from which <div style="margin-left: 40px;"> A fir, 10 ins. diam., bears East, 60 lks. dist., mkd. 1/4 S7 BT. A fir, 33 ins. diam., bears S. 32° W., 51 lks. dist., mkd. 1/4 S12 BT. </div> <hr style="width: 20%; margin: 20px auto;"/> N. 0° 15' W., beginning new measurement. Descend 40 ft. over NE. slope.
.65	Ravine, drains S. 85° E.; asc. 20 ft. over SE. slope.
2.35	Spur, slopes N. 80° E.; desc. 80 ft. over NE. slope.
4.80	Ravine, drains E.; asc. 30 ft. over SE. slope.
8.30	Spur, slopes E.; desc. 290 ft. over NE. slope.
15.30	Hubbard Creek Road, paved, 50 lks. wide, in curve, bears N. 60° W., and S. 45° E.
17.05	Hubbard Creek, 40 lks. wide, course N. 70° W.; asc. 120 ft. over SW. slope.