15203 Dependent Resurvey of a Portion of the East Boundary, T. 26 S., R. 8 W., Willamette Meridian, Oregon.

CHAINS	
31.45	Ravine, drains S. 70° W.; asc. 50 ft. over SW. slope.
33.85	Spur, slopes S. 70° W.; desc. 25 ft. over NW. slope.
40.38	Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. 1/4 S 1 | S 6 T 26 S R 8 W R 7 W 1971
	from which
	A fir, 15 ins. diam., bears N. 33° E., 27 lks. dist., mkd. 1/4 S6 BT.
	A fir, 20 ins. diam., bears S. 42° E., 26 lks. dist., mkd. 1/4 S6 BT.
	No other suitable trees available within limits.
	Descend 95 ft. over NW. slope, through heavy timber and dense undergrowth.
45.05	Creek, 3 lks. wide, course N. 50° W.; asc. 105 ft. over SW. slope.
49.15	Spur, slopes S. 75° W.; desc. 40 ft. over NW. slope.
50.65	Ravine, drains N. 85° W.; asc. 20 ft. over SW. slope.
51.70	Green Butte Road, 10 lks. wide, bears N. 60° E., and S. 60° W.
54.05	Spur, slopes S. 80° W.; desc. 100 ft. over NW. slope.
60.53	Point for the N 1/16 sec. cor. of secs. 1 and 6.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. N 1/16 S 1 | S 6 1971
	from which
	A fir, 20 ins. diam., bears N. 71° E., 36 lks. dist., mkd. N 1/16 S6 BT.
	A fir, 17 ins. diam., bears N. 36° W., 46 lks. dist., mkd. N 1/16 S1 BT.
	Descend 175 ft. over NW. slope.
67.55	Creek, 1 lk. wide, course N. 50° W., asc. 50 ft. over SW. slope.
68.55	Spur, slopes N. 80° W., desc. 90 ft. over NW. slope.
71.45	Creek, 3 lks. wide, course N. 64° W., asc. 90 ft. over SW. slope.