

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the East Boundary,  
T. 26 S., R. 8 W., Willamette Meridian, Oregon

15204

**CHAINS**

- 74.55 Spur, slopes S. 60° W., desc. 110 ft. over NW. slope.
- 78.75 Ravine, drains N. 75° W.; asc. 15 ft. over SW. slope.
- 80.93 Point for the cor. of Tps. 25 and 26 S., Rs. 7 and 8 W.,  
at proportionate distance; there is no remaining evidence  
of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.  
in the ground, with brass cap mkd.

T 25 S  
R 8 W R 7 W  
S 36 | S 31  
S 1 | S 6  
T 26 S  
1971

from which

- A fir, 10 ins. diam., bears N. 22° E., 87 lks.  
dist., mkd. T25S R7W S31 BT.
- A fir, 15 ins. diam., bears S. 49° E., 44 lks.  
dist., mkd. T26S R7W S6 BT.
- A fir, 20 ins. diam., bears S. 14° W., 52 lks.  
dist., mkd. T26S R8W S1 BT.
- A fir, 10 ins. diam., bears N. 45° W., 23 lks.  
dist., mkd. T25S R8W S36 BT.

From this point, the cor. of secs. 5, 6, 31, and 32, on the N.  
bdy. of T. 26 S., R. 7 W., bears S. 89° 34' E.,  
80.06 chs. dist., monumented with an iron post, 2 1/2 ins.  
diam., firmly set, protruding 4 ins. above ground, with  
brass cap mkd.

T 25 S R 7 W  
S 31 | S 32  
S 6 | S 5  
T. 26 S  
1971

from which the remains of the original bearing trees

- A root hole, bears N. 78° E., 11 lks. dist.,
- A root hole, bears S. 35° E., 64 lks. dist.

and trees mkd. by Grant, in 1958.

- A fir, 26 ins. diam., bears N. 2 1/2° E., 43 lks.  
dist., with scribe marks S32 T25S R7W BT visible  
on bark blaze.
- A fir, 11 ins. diam., bears S. 30° E., 18 lks.  
dist., with healed blaze.
- A fir, 7 ins. diam., bears S. 49° W., 26 lks.  
dist., with healed blaze.
- A madrone, 10 ins. diam., bears N. 55° W., 9 lks.  
dist., with scribe marks S31 T25S R7W visible  
on bark blaze.

and new bearing tree