

County Surveyor's Record, Douglas County, Oregon

15205

Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 8 W., Willamette Meridian, Oregon.

CHAINS

A fir, 5 ins. diam., bears N. 78° E., 43 lks.
dist., mkd. X BT.

A fir, 37 ins. diam., bears N. 12° W., 72 lks.
dist., mkd. T25S R7W S31 BT.

This control line was fully retraced, and careful search was made for evidence of intervening corners, none of which was recovered.

Land, mountainous.
Soil, clay loam.
Timber, fir, hemlock, cedar, madrone, alder, maple, and chinquapin; undergrowth, vine maple, salal, fern, rhododendron, and poison oak.

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 8 W., Willamette Meridian, Oregon.

(Restoring the 1874 survey by William H. Byars,
Deputy Surveyor, and
the 1881 retracement by Addison R. and Samuel C. Flint,
Deputy Surveyors)


N. 0° 46' W., bet. secs. 31 and 36.

Ascend 10 ft. over SW. slope, through heavy timber and light undergrowth.

- 2.30 Spur, slopes N. 55° W.; desc. 215 ft. over NW. slope.
 - 20.10 Wire fence, bears E. and W.
 - 21.70 Leave heavy timber, enter open fields, edge bears E. and W.
 - 26.60 Hubbard Creek, 40 lks. wide, course N. 55° E.; desc. 5 ft. over nearly level ground.
 - 32.65 Hubbard Creek, 40 lks. wide, course N. 55° W.; desc. 10 ft. over nearly level ground.
 - 38.43 Point selected for the witness 1/4 sec. cor. of secs. 31 and 36.
- Set an iron post, 28 ins. long, 2 1/2 ins diam., 24 ins. in the ground, with brass cap mkd.

FD OK PER JOHNSTONE
APRIL -87 M104-15

FD OK JUNE -94 By DeGroot
M119-33



from which

A myrtle, 12 ins. diam., bears N. 13° E., 188 lks.
dist., mkd. X BT.

An alder, 11 ins. diam., bears S. 80° W., 17 1/2 lks.
dist., mkd. X BT.