

County Surveyor's Record, Douglas County, Oregon

15207

Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 8 W., Willamette Meridian, Oregon.

CHAINS

Land, rolling hills.
Soil, sandy clay.
Timber, fir, hemlock, cedar, maple, myrtle, chinquapin,
alder, and madrone; undergrowth, fern, vine maple, salal,
rhododendron, hazel, and poison oak.

Dependent Resurvey of a Portion of the North Boundary,
T. 26 S., R. 8 W., Willamette Meridian, Oregon.

(Restoring the 1881 survey by Addison R. and
Samuel C. Flint, Deputy Surveyors)

N. 89° 45' W., bet. secs. 1 and 36, marking and blazing
the true line.

Descend 200 ft. over SW. slope, through heavy timber and
light undergrowth.

11.25 Hubbard Creek, 40 lks. wide, course N. 10° E.; asc. 85 ft.
over NE. slope, also leave heavy timber, enter open
field, edge bears N. and S.

16.35 Hubbard Creek, Road, paved 50 lks. wide, bears N. 30° E.,
and S. 30° W.

16.70 Wire fence, bears N. 30° E., and S. 30° W.

20.08 Point for the E 1/16 sec. cor. of secs. 1 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins.
in the ground, and in a mound of stone, 3 ft. base, to
top, with brass cap mkd.

E 1/16 $\frac{S\ 36}{S\ 1}$
1971

from which

A fir, 15 ins. diam., bears N. 47° W., 69 lks.
dist., mkd. E 1/16 S36 BT.

No other suitable tree available within limits.

Ascend 405 ft. over NE. slope.

20.35 Wire fence, bears N. and S.

23.30 Enter heavy timber, edge bears N. and S.

40.16 The 1/4 sec. cor. of secs. 1 and 36, perpetuated and
recorded by the County Surveyor, in 1971, monumented
with an iron post, 2 ins. diam., firmly set, protruding
10 ins. above ground, with brass cap mkd.

T 25 S R
1/4 $\frac{S\ 36}{S\ 1}$ 8
T 26 S W
1971

from which the remains of the original bearing tree

A fir stump, 30 ins. diam., bears S. 35° E., 40 lks.
dist., with fragmentary scribe marks visible on
weathered bark blaze.