

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the North Boundary,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

15209

CHAINS

Timber, fir, hemlock, cedar, maple, chinquapin, and madrone; undergrowth, salal, fern, rhododendron, hazel, vine maple, and poison oak.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the 1881 survey by Addison R. and Samuel C. Flint, Deputy Surveyor, and the 1896 survey by William P. Heydon, Deputy Surveyor)

The cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

T 26 S
R 8 W R 7 W
S 24 | S 19
S 25 | S 30
1959

from which

A mound of stone, 3 1/2 ft. base, 2 ft. high, bears West, 2 lks. dist.

N. 89° 34' W., bet. secs. 24 and 25.

Ascend 820 ft. over SE. slope, through heavy reproduction and dense undergrowth.

12.35 Dirt road, 15 lks. wide, bears N. 40° W., and S. 40° E.

22.80 Spur, slopes N. 80° W., desc. 80 ft. over W. slope.

40.39 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4 S 24
S 25
T 26 S R 8 W
1971

from which

A fir, 25 ins. diam., bears N. 26° E., 63 lks. dist., mkd. 1/4 S24 BT.

A fir, 5 ins. diam., bears S. 68° W., 18 lks. dist., mkd. X BT.

Descend 735 ft. over W. slope.

42.30 Gravelled road, 25 lks. wide, bears N. 20° W., and S. 20° E.

80.78 The cor. of secs. 23, 24, 25, and 26, perpetuated and recorded by the County Surveyor, in 1968, monumented