

County Surveyor's Record, Douglas County, Oregon

15211

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

22.50

Dirt road, 20 lks. wide, bears S. 25° W., and N. 25° E.


40.22

The 1/4 sec. cor. of secs. 23 and 24, determined at record bearing and distance, from the remains of the original bearing tree.

A fir, 50 ins. diam., bears N. 20° E., 88 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.



from which new bearing trees

An alder, 5 ins. diam., bears S. 88° E., 31 lks.
dist., mkd. 1/4 S24 BT.

A fir, 16 ins. diam., bears N. 29° W., 49 lks.
dist., mkd. 1/4 S23 BT.

N. 0° 19' E., beginning new measurement.

Descend 5 ft. over NW. slope.

0.15

Lake Creek, 10 lks. wide, course W.; asc. 5 ft. over S. slope.


1.40

Creek, 4 lks. wide, course S. 10° W.; asc. 650 ft. over SW. slope.

19.965

Point for the N 1/16 sec. cor. of secs. 23 and 24.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 35 ins. diam., bears S. 14 1/2° E., 149 lks.
dist., mkd. N 1/16 S24 BT.

An alder, 9 ins. diam., bears N. 53° W., 68 lks.
dist., mkd. N 1/16 S23 BT.

Ascend 165 ft. over SW. slope.

28.80

Spur, slopes W.; desc. 135 ft. over NW. slope.

29.70

Dirt road, 15 lks. wide, bears E. and W.

39.93

The cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 10 ins. above ground, with brass cap mkd.