

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 26 S., R. 8 W., Willamette Meridian, Oregon

15214

CHAINS

from which the remains of the original bearing trees

A hemlock, 27 ins. diam., bears N. 63° E., 28 lks. dist., with healed balze, re-marked by County Surveyor, 1/4 S13 CS BT visible on open double blaze.

A decayed hemlock stump, 9 ins. diam., bears N. 23° W., 23 lks. dist., with scribe marks BT visible on opened blaze.

and a bearing tree mkd. by Tracy, in 1968

A fir, 45 ins. diam., bears N. 86° W., 39 lks. dist., with scribe marks 1/4 S14 CS BT visible on open blaze.

N. 0° 03' E., beginning new measurement.

Ascend 80 ft. over SE. slope..

13.80 Spur, slopes S. 45° W.; desc. 40 ft. along W. slope.

17.40 Dirt road, 30 lks. wide, bears S. 10° W., and N. 10° E.

22.10 Ravine, drains W.; asc. 190 ft. over SW. slope.

29.50 Dirt road, 30 lks. wide, bears N. 50° W., and S. 50° E.

31.35 Same dirt road, 30 lks. wide, in curve, bears N. 15° E., and S. 15° E.,

40.32 The cor. of secs. 11, 12, 13, and 14, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.

T 26 S
S 11 S 12
S 14 S 13
R 8 W
1968

from which the remains of the original bearing tree

A hemlock, 15 ins. diam., bears N. 48° E., 28 lks. dist., with scribe makrs 26S R8W visible on partially healed balze, (Record, N. 52° E., 27 lks.)

A fir, 47 ins. diam., bears S. 60° E., 56 lks. dist., with healed blaze.

A chinquapin, 27 ins. diam., bears S. 53° W., 60 lks. dist., with fragmentary scribe marks visible on partially healed blaze, re-marked by the County Surveyor, in 1968, with scribe marks T26S R8W S14 CS BT visible on open blaze.

and bearing trees mkd. by Tracy, in 1968

A hemlock, 18 ins. diam., bears N. 18° E., 42 lks. dist., with scribe marks T26S R8W S12 CS BT visible on open blaze.