

County Surveyor's Record, Douglas County, Oregon

15215

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 26 S., R. 8 W., Willamette Meridian, Oregon.

CHAINS

A hemlock, 18 ins. diam., bears S. 59° E., 50 lks. dist., with scribe marks T26S R8W S13 CS BT. visible on open blaze.

A fir, 5 ins. diam., bears N. 74 1/2° W., 27 lks. dist., with fragmentary scribe marks visible on pitched over blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, chinquapin, and madrone; undergrowth, salal, fern, rhododendron, hazel, vine maple, and poison oak.

From the true point for the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of the Tp.

S. 89° 52' W., bet. secs. 12 and 13.

Ascend 285 ft. over E. slope. through heavy reppodution and dense undergrowth.

5.70 Spur ridge, bears N. 75° W. and S. 75° E.; desc. 45 ft. over NW. slope.

6.85 Dirt road, 25 lks. wide, bears N. and S.

9.00 Ravine, drains N.; asc. 240 ft. over NE. slope.

19.94 Point for the E 1/16 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 12}{S\ 13}$
1971

from which

A fir, 25 ins. diam., bears N. 19° E., 31 lks. dist., mkd. E 1/16 S12 BT.

A fir, 16 ins. diam., bears S. 20° W., 17 lks. dist., mkd. E 1/16 S13 BT.

Ascend 250 ft. over NE. slope.

39.88 The 1/4 sec. cor. of secs. 12 and 13, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

T 26 S
1/4 $\frac{S\ 12}{S\ 13}$
R 8 W
1968

from which the original bearing trees

A fir, 42 ins. diam., bears S. 68° W., 11 lks. dist., with scribe mark B visible on bark blaze and re-marked by Tracy, in 1968, with scribe marks 1/4 S13 CS BT visible on open blaze. (Record, N. 68° E.)