

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines.
T. 26 S., R. 8 W., Willamette Meridian, Oregon

15216

CHAINS

A fir, 33 ins. diam., bears N. 62° W., 16 lks. dist., with scribe mark 1/4 visible on weathered bark blaze.

and a bearing tree mkd. by Tracy, in 1968

A fir, 30 ins. diam., bears N. 4° W., 11 lks. dist, with pitched over blaze.

N. 89° 45' W., beginning new measurement.

Ascend 85 ft. over E. slope.

4.55 Spur, slopes S.; desc. 25 ft. over W. slope.

5.25 Ravine, drains N. 45° W.; asc. 180 ft. over E. slope.

19.10 Spur, slopes S.; desc. 15 ft. over SW. slope.

20.90 Ravine, drains S.; asc. 185 ft. over SE. slope.

33.86 An original line tree; a fir, 68 ins. diam., mkd. with 2 hacks on E. and W. sides.

N. 89° 45' W., beginning new measurement.

2.39 Top of ascent, slopes S.; desc. 10 ft. over W. slope.

6.37 The cor. of secs. 11, 12, 13, and 14.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, maple, chinquapin, and madrone; undergrowth, salal, fern, rhododendron, hazel, vine maple, and poison oak.

From the cor. of secs. 1 and 2 only, on the N. bdy. of sec. 12, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

T 26 S
S 2 | S 1
R 8 W
1968

from which the remains of the original bearing trees

A root hole, bears N. 60° E., 58 lks. dist.

A fir snag, 52 ins. diam., bears S. 85° W., 28 lks. dist, with fragmentary scribe marks visible on burned and weathered bark blaze.

and bearing trees mkd. by Tracy in 1968

A hemlock, 9 ins. diam., bears N. 57° E., 38 lks. dist., with scribe marks T26S R8W S1 CS BT. visible on open blaze.

A hemlock, 9 ins. diam., bears N. 43° W., 38 lks. dist., with scribe marks T26S R8W S2 CS BT visible on open blaze.

S. 89° 23' W., on the S. bdy. of sec. 2.