

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 26 S., R. 8 W., Willamette Meridian, Oregon.

15218

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

1/4
S 11 | S 12
T 26 S R 8 W
1971

from which new bearing trees

A fir, 7 ins. diam., bears N. 86° E., 27 lks. dist., mkd. 1/4 S12 BT.

A fir, 13 ins. diam., bears N. 49° W., 41 1/2 lks. dist., mkd. 1/4 S11 BT.

N. 0° 03' W., beginning new measurement.

Descend 300 ft. over N. slope.

20.935 Point for the N 1/16 sec. cor. of secs. 11 and 12.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16
S 11 | S 12
1971

from which

A hemlock, 12 ins. diam., bears N. 75° E., 53 lks. dist., mkd. N 1/16 S12 BT.

A cedar, 21 ins. diam., bears S. 81 1/2° W., 33 lks. dist., mkd. N 1/16 S11 BT.

Descend 150 ft. over N. slope.

25.30 Creek, 2 lks. wide, course W.; asc. 70 ft. over S. slope.

29.00 Spur, slopes W.; desc. 450 ft. over N. slope.

41.20 Dirt road, 25 lks. wide, bears N. 40° E., and S. 40° W.

41.87 The original closing cor. of secs. 11 and 12, on the S. bdy. of secs. 2, perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1968, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 26 S
C C

S 11 | S 12
R 8 W
1968

from which the remains of the original bearing trees

A fir snag, 26 ins. diam., bears S. 74° E., 43 lks. dist., with scribe marks T26S R 12 BT visible on weathered bark blaze.

A sawed hemlock stump, 15 ins. diam., bears S. 63° W., 29 lks. dist., with scribe marks T26S R8W S11 visible on opened blaze.