

County Surveyor's Record, Douglas County, Oregon

15225

Dependent Resurvey of a Portion of the South Boundary,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

S. 87° 39' W., bet. secs. 3 and 34.

Descend 145 ft. over SW. slope, through scattering timber and dense undergrowth.

6.45 Creek, 3 lks. wide, course S. 10° E.; asc. 140 ft. over NE. slope.

13.45 Spur, slopes S. 20° E.; desc. 220 ft. over SW. slope.

20.85 Dirt road, 15 lks. wide, bears S. 10° E. and N.20° W.

24.05 Creek, 3 lks. wide, course S. 20° E.; asc. 230 ft. over NE. slope.

31.45 Spur, slopes S. 10° E.; desc. 70 ft. over SW. slope.

35.40 Draw, drains S. 10° W.; asc. 140 ft. over SE. slope.

39.08 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

No permanent monument set.

Ascend 25 ft. over SE. slope.

42.70 Spur, slopes S. 10° W.; desc. 45 ft. over SW. slope.

47.40 Draw, drains S. 5° W.; asc. 50 ft. over SE. slope.

52.30 Spur, slopes S. 40° W.; desc. 165 ft. over SW. slope.

62.60 Creek, 3 lks. wide, course S. 10° W.; asc. 165 ft. over SE. slope.

76.00 Spur, slopes S. 20° W.; desc. 35 ft. over W. slope.

78.16 Point for the cor. of secs. 3, 4, 33, and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

| | | | | | |
|---|----|----|---|----|------|
| T | 30 | S | R | 8 | W |
| | S | 33 | S | 34 | |
| | S | 4 | S | 3 | |
| | T | 31 | S | | |
| | | | | | 1972 |

from which

A sugar pine, 15 ins. diam., bears N. 33 1/2° E.,
51 lks. dist., mkd. T30S R8W S34 BT.

A white fir, 6 ins. diam., bears S. 22° E., 19 1/2
lks. dist., mkd. T31S R8W S3 BT.

A white fir, 8 ins. diam., bears S. 37 1/2° W., 24
lks. dist., mkd. T31S R8W S4 BT.

A white fir, 8 ins. diam., bears N. 49 1/2° W., 32
lks. dist., mkd. T30S R8W S33 BT.

Land, mountainous.