| CHAINS | |
|---|---|
| | from which the original bearing trees<br><br>A sugar pine, 29 ins. diam., bears N. 25° E., 8 lks. dist., with healed blaze.<br><br>A sugar pine, 26 ins. diam., bears S. 48° E., 82 lks. dist., with scribe marks T30S R8 visible on opened blaze. (Record, 80 lks.)<br><br>and bearing trees mkd. by Byron, in 1965<br><br>A sugar pine, 13 ins. diam., bears N. 46° E., 77 lks. dist., with scribe marks S R8W visible on partially healed blaze.<br><br>A chinquapin, 6 ins. diam., bears S. 60° E., 35 1/2 lks. dist., with scribe marks S29 T30S R8W CS BT visible on open blaze.<br><br>A chinquapin, 6 ins. diam., bears S. 22° W., 21 lks. dist., with scribe marks S30 CS BT visible on open blaze.<br><br>A fir, 15 ins. diam., bears N. 83° W., 30 1/2 lks. dist,, with healed blaze.<br><br>N. 0° 02' E., bet. secs. 19 and 20, marking and blazing the true line.<br><br>Descend 210 ft. over general N. slope, through heavy timber and moderate undergrowth. |
| 14.60 | Boulder Creek, 4 lks. wide, course West; asc. 30 ft. over S. slope. |
| 19.45 | Boulder Creek Road, gravelled, 24 lks. wide, bears E. and W. |
| 19.87 | Point for the S 1/16 sec. cor. of secs. 19 and 20.<br><br>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.<br><br>S 1/ 16<br>S 19\|S 20<br>1972<br><br>from which<br><br>A white fir, 8 ins. diam., bears N. 32 1/2° E., 24 1/2 lks. dist., mkd. S 1/16 S20 BT.<br><br>A fir, 15 ins. diam., bears N. 56 1/2° W., 67 1/2 lks. dist., mkd. S 1/16 S19 BT.<br><br>Ascend 385 ft. over S. slope. |
| 39.74 | Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.<br><br>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.<br><br>T 30 S R 8 W<br>1/4<br>S 19\|S 20<br>1972 |