

County Surveyor's Record, Douglas County, Oregon

15228

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 20 ins. diam., bears S. 75° E., 49 lks.
dist., mkd. 1/4 S20 BT.

A fir, 18 ins. diam., bears West, 45 lks. dist.,
mkd. 1/4 S19 BT.

Ascend 205 ft. over SE. slope.

49.50 Enter logged area, edge bears N. and W.

54.30 Rock bluff, 50 ft. high, faces East; continue ascent
over SE. slope.

59.00 Spur, slopes E.; desc. 50 ft. over NE. slope.

67.60 Draw, drains E.; asc. 90 ft. over SE. slope, also leave
logged area, edge bears S. and W.

76.25 Spur, slopes E.; desc. 35 ft. over NE. slope.

79.48 The cor. of secs. 17, 18, 19, and 20, perpetuated and
recorded by Vernon Tracy, Deputy County Surveyor, in
1965, monumented with an iron post, 1 in. diam., firmly
set, protruding 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S R 8 W

S 18 | S 17

S 19 | S 20

1965

from which the remains of the original bearing trees

A root hole, bears N. 74° E., 31 lks. dist., with
a down oak alongside, 10 ins. diam., with healed
blaze.

A madrone, 24 ins. diam., bears S. 11° E., 59 lks.
dist., with fragmentary scribe marks visible
on opened blaze.

A root hole, bears S. 44° W., 59 lks. dist., with
a down madrone alongside, 16 ins. diam., with
fragmentary scribe marks visible on decayed blaze.

An oak, 15 ins. diam., bears N. 10° W., 65 lks.
dist., no marks visible on decayed blaze.

and bearing trees mkd. by Tracy

A cedar, 22 ins. diam., bears N. 11° E., 48 lks.
dist., with scribe marks T30S R8W S17 CS BT.
visible on open blaze.

A white fir, 16 ins. diam., bears S. 1° E., 29 lks.
dist., with scribe marks T30 R8W S20 CS BT.
visible on open blaze.

A fir, 10 ins. diam., bears S. 31° W., 35 lks.
dist., with healed blaze.

A white fir, 17 ins. diam., bears N. 59° W., 14 1/2
lks. dist., with healed blaze.

Land, mountainous.