

County Surveyor's Record, Douglas County, Oregon

15232

Dependent Resurvey of a Portion of the East Boundary,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

	S 13	S 18	T 24 S
R 6 W	S 24	S 19	R 5 W

 1959

from which the remains of bearing trees mkd. by Frear

A root hole, bears N. 62 1/2° E., 49 lks. dist.

A black oak, 18 ins. diam., bears S. 44° E., 65 lks. dist., with healed blaze.

A white oak, 17 ins. diam., bears N. 54° W., 46 lks. dist., with healed blaze. This tree was rescribed by Byron, in 1960, and has healed blaze.

and bearing trees mkd. by Byron

A white oak, 12 ins. diam., bears N. 42° E., 86 lks. dist., with healed double blaze.

A white oak, 18 ins. diam., bears S. 41° W., 67 lks. dist., with healed double blaze.

N. 0° 14' E., bet. secs. 13 and 18, marking and blazing the true line.

Ascend over rolling and broken land, through light to moderate timber and undergrowth.

Ascend 60 ft. over S. slope.

6.30 Ridge, bears E. and W.; desc. 330 ft. over NE. slope.

33.45 Wheeler Canyon, drains S. 20° E.; asc. 60 ft. over S. slope.

40.15 Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 24 S
 R 6 W R 5 W
 1/4
 S 13 | S 18
 1973

from which

A white oak, 20 ins. diam., bears N. 52° E., 21 lks. dist., mkd. 1/4 S18 BT.

A white oak, 16 ins. diam. bears N. 58 1/2° W., 29 1/2 lks. dist., mkd. 1/4 S13 BT.

Ascend 225 ft. over SW. slope.

60.225 Point for the N 1/16 sec. cor. of secs. 13 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16
 S 13 | S 18
 1973