

County Surveyor's Record, Douglas County, Oregon

15234

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 15.90 | <p>Descent 75 ft. over NW. slope, through light to moderate timber and undergrowth.</p> <p>Ravine, drains, S.; asc. 110 ft. over NW. slope.</p> |
| 25.10 | <p>Ridge, bears N. and S.; desc. 200 ft. over SW. slope.</p> |
| 40.06 | <p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T 24 S R 6 W 1/4 <u>R 13</u> R 24 1973</p> |
| | <p>from which</p> <p style="padding-left: 40px;">A white oak, 10 ins. diam., bears N. 43 1/2° E., 17 lks. dist., mkd. 1/4 S13 BT.</p> <p style="padding-left: 40px;">A white oak, 12 ins. diam., bears S. 69 1/2° E., 34 lks. dist., mkd. 1/4 S24 BT.</p> |
| | <p>Descend 20 ft. over SW. slope.</p> |
| 43.00 | <p>Ravine, drains S.; asc. 130 ft. over NE. slope.</p> |
| 51.90 | <p>Spur, slopes S.; desc. 25 ft. over W. slope.</p> |
| 58.30 | <p>Ravine, drains S.; asc. 140 ft. over E. slope.</p> |
| 80.12 | <p>The cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by F. C. Frear, Deputy County Surveyor, in 1919, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 24 S R 6 W S 14 S 13 S 23 S 24 1958</p> |
| | <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A white oak, 36 ins. diam., bears S. 12 1/2° E., 118 lks. dist., no marks visible on burned and decayed blaze.</p> <p style="padding-left: 40px;">A root hole, bears S. 45° W., 93 lks. dist., with a down white oak alongside, 34 ins. diam., no marks visible on decayed blaze.</p> |
| | <p>and the remains of bearing trees mkd. by Frear</p> <p style="padding-left: 40px;">A fir stump, 24 ins. diam., bears North, 84 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 19° E., 38 lks. dist., with healed double blaze.</p> |