

County Surveyor's Record, Douglas County, Oregon

15236

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 8 ins. diam., bears N. 62° E., 43 lks.
dist., mkd. N 1/16 S13 BT.

A black oak, 18 ins. diam., bears N. 86 1/2° W., 90
lks. dist., mkd. N 1/16 S14 BT.

Descend 190 ft. over NW. slope.

78.35

Ravine, drains N. 55° W.; asc. 15 ft. over general S.
slope.

80.14

The cor. of secs. 11, 12, 13, and 14, perpetuated and re-
corded by Vernon R. Tracey, Deputy County Surveyor, in
1970, monumented with an iron post, 1 1/2 ins. diam., firmly
set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S
S 11 | S 12
S 14 | S 13
R 6 W
1970

*from 80.14
to 80.14
719 + M120-42*

from which the remains of the original bearing trees

A white oak, 25 ins. diam., bears N. 73° E., 72
lks. dist., with healed blaze.

A white oak, 24 ins. diam., bears S. 79° E., 48
lks. dist., with healed blaze.

A white oak, 20 ins. diam., bears S. 38° W., 25
lks. dist., with fragmentary scribe marks visible
on partially healed blaze.

and bearing trees mkd. by Tracy

A fir, 13 ins. diam., bears N. 66° E., 35 lks.
dist., with healed blaze.

A white oak, 15 ins. diam., bears S. 9° E., 38
lks. dist., with scribe marks T24S R6W S13 CS
BT visible on partially healed blaze.

A fir, 50 ins. diam., bears S. 54° W., 19 lks.
dist., with scribe marks T24S R6W S14 CS BT
visible on bark.

A white oak, 9 ins. diam., bears N. 20° W., 44
lks. dist., with scribe marks T24S R6W S11 CS
BT visible on partially healed blaze.

Corner is located on a spur, slopes W.

Land, mountainous.

Soil, rocky clay loam.

Timber, cedar, hemlock, fir, oak, chinquapin, maple, and
madrone; undergrowth, huckleberry, hazel, vine maple,
rhododendron, poison oak, fern, blackberry, manzanita,
arrowwood, and salal.

From the cor. of secs. 7, 12, 13, and 18, on the E. bdy.
of the Tp.