

# County Surveyor's Record, Douglas County, Oregon

15238

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	Descend 10 ft. over N. slope, through light to moderate timber and undergrowth.
3.10	Ravine, drains S. 50° W.; asc. 90 ft. over SE. slope.
8.95	Ridge, bears E. and W.; desc. 90 ft. over NW. slope.
20.07	Point for the S 1/16 sec. cor. of secs. 11 and 12.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     S 1/16                      S 11   S 12                      1973                 </div> from which  <div style="margin-left: 40px;">                         A fir, 15 ins. diam., bears N. 61° E., 39 lks. dist., mkd. S 1/16 S12 BT.                           A white oak, 7 ins. diam., bears N. 42° W., 30 lks. dist., mkd. S 1/16 S11 BT.                     </div> Descend 70 ft. over NW. slope.
24.90	Ravine, drains W.; desc. 105 ft. over NW. slope.
31.10	Ravine, drains W.; asc. 30 ft. over SW. slope.
34.60	Top of ascent, slopes W.; desc. 60 ft. over N. slope.
40.14	The 1/4 sec. cor. of secs. 11 and 12, re-established by Don E. Garrett, RLS No. 544, monumented with an iron post 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground with brass cap mkd.  <div style="display: flex; justify-content: space-between;"> <div style="width: 30%; font-size: small;">                         FO OK                          8/92 Dolan                          M 115-49                          FU OK                          12/95 Dolan                          M. 21-48                     </div> <div style="width: 60%; text-align: center;">                         T 24 S R 6 W                          1/4                          S 11   S 12                          RPLS 544                          1973                     </div> </div> from which bearing trees mkd. by Garrett  <div style="margin-left: 40px;">                         A fir, 13 ins. diam., bears N. 41 1/2° E., 94 lks. dist., mkd. 1/4 S12 BT.                           A fir, 7 ins. diam., bears N. 74° W., 120 lks. dist., mkd. 1/4 S11 BT.                     </div> <hr style="width: 20%; margin-left: 40px;"/> N. 0° 13' E., beginning new measurement.  Descend 2ft. over N. slope.
0.05	Norton Creek, 5 lks. wide, course S. 68° W. to S. 38° W., from N.; asc. 65 ft. over S. slope.
40.13	The cor. of secs. 1, 2, 11, and 12, determined at record bearing and distance from which the remains of the original bearing trees:  <div style="margin-left: 40px;">                         A white oak, 26 ins. diam., bears N. 86° E., 80 lks. dist., with fragmentary scribe marks visible in negative on overgrowth.                     </div>