CHAINS	
	A fir, 12 ins. diam., bears N. 37° W., 31 1/2 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	and a new bearing tree.
	A fir, 7 ins. diam., bears S. 70 1/2° E., 89 lks. dist., mkd. T24S R6W S14 BT.
	Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, oak, maple, chinquapin, and madrone; undergrowth, huckleberry, hazel, vine maple, rhododendron, poison oak, fern, blackberry, manzanita, arrowwood, and salal.
	N. 0° 06' E., bet. secs. 10 and 11.
	Ascend 100 ft. over SW. slope, through light to moderate timber and undergrowth.
8.80	Spur, slopes W.; desc. 35 ft. over NW. slope.
14.20	Bottom of descent, slopes SW.; asc. 150 ft. over S. slope
16.75	Gravelled road, bears N. 15° E. and S. 10° W.
40.17	The 1/4 sec. cor. of secs. 10 and 11, established by Roseburg Lumber Co., in 1973, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground.
	At the corner point
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	1/4 S 10 | S 11 T 24 S R 6 W 1973
	from which
	An oak, 12 ins. diam., bears N. 39° E., 111 lks. dist., mkd. 1/4 S11 BT.
	An oak, 11 ins. diam., bears N. 77 1/4° W., 327 lks. dist., mkd. 1/4 S10 BT.
	Reset iron pipe alongside iron post.
	N. 0° 06' E., beginning new measurement.
	Ascend 220 ft. over S. slope.
1.60	Wire fence, extends E. and W.
14.20	Wire fence, extends N. 60° W. and S. 60° E.
15.90	Dirt road, 15 lks. wide, bears E. and W.
20.085	The N 1/16 sec. cor. of secs. 10 and 11, established by