

# County Surveyor's Record, Douglas County, Oregon

15242

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

Roseburg Lumber Co., in 1973, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 2 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16  
S 10 | S 11  
1973

from which

A fir, 7 ins. diam., bears N. 30 1/2° E., 132 lks. dist., mkd. N 1/16 S11 BT.

A cedar, 8 ins. diam., bears N. 30° W., 117 lks. dist., mkd. N 1/16 S10 BT.

Reset iron pipe alongside iron post.

N. 0° 06' E., beginning new measurement.

Ascend 475 ft. over S. slope.

15.80 Dirt road, 14 lks. wide, bears N. 38° E. and S. 38° W.

20.085 The cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by James W. Bryon, Deputy County Surveyor, in 1958, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

S 3 | S 2  
S 10 | S 11  
T 24 S R 6 W  
1958

from which the remains of the original bearing trees

A root hole, bears N. 50° E., 20 lks. dist.

A laurel stump, 30 ins. diam., bears S. 5° E., 108 lks. dist., no marks visible on burned blaze.

~~A laurel stump, 30 ins. diam., bears S. 5° E., 108 lks. dist., no marks visible on burned blaze.~~

A fir snag, 30 ins. diam., bears S. 67° W., 68 lks. dist., with scribe marks 10 visible on partially healed blaze.

A root hole, bears N. 75° W., 51 lks. dist.

and the remains of bearing trees mkd. by Bryon

A root hole, bears N. 25° E., 22 lks. dist., with a down fir alongside, 27 ins. diam., with healed blaze.

A fir, 34 ins. diam., bears S. 55° E., 5 lks. dist., with healed blaze.

A cedar, 48 ins. diam., bears S. 42° W., 131 lks. dist., with scribe marks T24S R6W S10 CS BT visible on partially healed blaze.