

County Surveyor's Record, Douglas County, Oregon

15244

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS							
40.11	<p>The cor. of secs. 2,3, 10, and 11.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, cedar, fir, hemlock, chinquapin, maple, oak, and madrone; undergrowth, huckleberry, haqel, vine maple, poison oak, fern, blackberry, manzanita, arrowwood, and salal.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23, determined at record bearing and distance from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A white oak, 30 ins. diam., bears N. 57° E., 31 lks. dist., with scribe marks BT visible on open blaze.</p> <p style="padding-left: 40px;">A white oak, 48 ins. diam., bears S. 7 3/4° E., 306 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A white oak, 36 ins. diam., bears N. 45° W., 47 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by James W. Bryon, Deputy County Surveyor, in 1958</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 5° E., 57 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A white oak, 11 ins. diam., bears S. 81° E., 55 1/2 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A white oak, 8 ins. diam., bears S. 65° W., 40 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A white oak, 14 ins. diam., bears N. 46° W., 16 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 S R 6 W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 15</td> <td style="padding: 0 5px;">S 14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 22</td> <td style="padding: 0 5px;">S 23</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1973</td> </tr> </table> </div> <p>N. 89° 57' W., bet. secs. 15 and 22.</p> <p>Descend 15 ft. over W. slope, through light to moderate timber and undergrowth.</p>	S 15	S 14	S 22	S 23	1973	
S 15	S 14						
S 22	S 23						
1973							
0.75	Norton Creek, 10 lks. wide, course S. 40° W.; asc. 375 ft. over SE. slope.						
2.45	Wire fence, extends N. 10° E. and S. 10° W.						
10.45	Gravelled road, 25 lks. wide, bears N. 20° E. and S. 10° W.						
20.50	Wire fence, extends N. 10° E. and S. 10° E. and S. 10° W.						
40.14	Point for the 1/4 sec. cor. of secs. 15 and 22, at proportionate distance; there is no remaining evidence of the original corner.						