

# County Surveyor's Record, Douglas County, Oregon

15245

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4       $\frac{S\ 15}{S\ 22}$   
T 24 S R 6 W  
1973

from which

A white oak, 23 ins. diam., bears N. 30° E., 303 lks. dist., mkd. 1/4 S15 BT.

A white oak, 15 ins. diam., bears S. 78° W., 184 1/2 lks. dist., mkd. 1/4 S22 BT.

Ascend 160 ft. over SE. slope.

51.45      Spur, slopes S.; desc. 425 ft. over NW. slope; also wire fence, extends N. 45° E. and S. 45° W.

77.70      Wire fence, extends N. 20° W. and S. 20° E.

79.65      Wire fence, extends S. 60° W. and N. 60° E.

80.28      The cor. of secs. 15, 16, 21, and 22, perpetuated and recorded by James W. Bryon, Deputy County Surveyor, in 1958, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

$\frac{S\ 16}{S\ 21}$  |  $\frac{S\ 15}{S\ 22}$   
T 24 S R 6 W  
1958

from which the remains of the original bearing trees

A sawed fir stump, 48 ins. diam., bears S. 17° W., 132 lks. dist., with a down fir log alongside, no marks visible on decayed blaze.

and bearing trees mkd. by Bryon

A white oak, 13 ins. diam., bears N. 63 1/2° E., 250 lks. dist., with healed blaze.

A white oak, 10 ins. diam., bears S. 33 1/2° E., 68 lks. dist., with healed blaze.

A fir, 21 ins. diam., bears S. 65° W., 285 1/2 lks. dist., with healed blaze.

An ash, 33 ins. diam., bears N. 15 1/2° W., 252 1/2 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, oak, hemlock, maple, chinquapin, and madrone; undergrowth, huckleberry, hazel, vine maple, poison oak, fern, blackberry, manzanita, arrowwood, and salal.

N. 0° 13' E., bet. secs. 15 and 16.