

County Surveyor's Record, Douglas County, Oregon

15246

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 240 ft. over SW. slope, through light to moderate timber and undergrowth.
4.40	Wire fence extends E. and W.
11.15	Spur, slopes S. 50° W.; asc. 30 ft. over S. slope. bears E.
19.70	Wire fence, extends E. and W.; enter heavy timber, edge bears E. and W.
25.65	Spur, slopes W.; desc. 70 ft. over NW. slope.
31.40	Ravine, drains W.; asc. 140 ft. over SW. slope.
40.12	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} 1/4 \\ S\ 16\ \ S\ 15 \\ T\ 24\ S\ R\ 6\ W \\ 1973 \end{array}$
	from which
	A fir, 11 ins. diam., bears N. 48 1/2° E., 68 lks. dist., mkd. 1/4 S15 BT.
	A fir, 8 ins. diam., bears S. 56 1/2° W., 90 lks. dist., mkd. 1/4 S16 BT.
	Ascend 15 ft. over SW. slope.
41.55	Spur, slopes S. 60° W.; desc. 90 ft. over NW. slope.
47.40	Bottom of descent, slopes W.; asc. 220 ft. over SW. slope.
53.00	Leave heavy timber, edge bears E. and W.
59.80	Wire fence, extends E. and W.
80.24	The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by James W. Bryon, Deputy County surveyor, in 1958, and redescribed by C. Albert White and Norman J. McDonald, Cadastral Surveyors, in 1963, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	<p>COUNTY SURVEYORS OFFICE</p> $\begin{array}{c} S\ 9\ \ S\ 10 \\ S\ 16\ \ S\ 15 \\ T\ 24\ S\ R\ 6\ W \\ 1958 \end{array}$
	From which the remains of the bearing trees mkd. by Williams R. Whipple, Deputy Surveyor, in 1891
	A cedar, 40 ins. diam., bears S. 7 3/4° E., 176 lks. dist., no marks visible on opened blaze.
	A root hole, bears S. 84° 10' W., 181 lks. dist., with a down cedar alongside, 48 ins. diam., with scribe marks T2 S visible on opened blaze.