

County Surveyor's Record, Douglas County, Oregon

15247

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

and bearing trees mkd. by Bryon

An apple, 13 ins. diam., bears N. 62 1/2° E., 191 lks. dist., with scribe marks S10 CS BT visible on bark. (Record, N. 61 1/4° E.)

A white oak, 21 ins. diam., bears S. 86° E., 388 lks. dist., with healed blaze.

A cedar, 14 ins. diam., bears S. 20 1/4° W., 88 lks. dist., with healed blaze.

A twin white oak, 28 ins. diam., bears S. 88° lks. 303 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, oak, cedar, hemlock, maple, chinquapin, and madrone; undergrowth, huckleberry, hazel, vine maple, poison oak, fern, blackberry, manzanita, arrowwood, and salal.

From the cor. of secs. 10, 11, 14, and 15.

N. 89° 47' W., bet. secs. 10 and 15.

Descend 60 ft. over W. slope, through light to moderate timber and undergrowth.

1.70 Gravelled road, 25 lks. wide. bears N. 10° E and S. 10° W.

2.40 Dry creed bed, 8 lks. wide, drains S. 25° W.; asc. 340 ft. over NE. slope.

18.60 Wire fence, extends N. and S.

18.70 Spur, slopes N. 15° W.; desc. 230 ft. over W. slope.

38.15 Dry cree~~k~~ bed, 3 lks. wide, drains S. 15° E.' asc. 30 ft. over E. slope.

40.02 The 1/4 sec. cor. of secs. 10 and 15, perpetuated by person (s) unknown, monumented with a wooden post, 4 ins. sq., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees:

A sawed fir stump, 48 ins. diam., bears S. 14° W., 30 lks. dist., no marks visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4 $\frac{S\ 10}{S\ 15}$
T 24 S R 6 W
1973

from which new bearing trees

A fir, 10 ins. diam., bears N. 79° E., 53 lks. dist., mkd. 1/4 S10 BT.

A fir, 6 ins. diam., bears S. 63° W., 20 lks. dist., mkd. 1/4 S15 BT.